



2000W




PICTURES



DETAILS



CONNECTION



SPEC.

Model	TP2000W-12V	TP2000W-24V	TP2000W-48V
Output power	2000W		
Peak power	4000W		
Input voltage(Range)	DC12V(9-15.5V)	DC24V(18-31V)	DC48V(38-61V)
Output voltage(Single)	(100VAC/110VAC/120VAC/220VAC/230VAC/240VAC) ±5%		
Unload current less than	≤0.7A	≤0.4A	≤0.3A
Output frequency	50Hz or 60Hz		
Output waveform	Pure sine wave		
Waveform distortion	THD≤3%(Pure resistive Load)		
USB	18W Fast charging		/
Max.output efficiency	88%	90%	92%
Low voltage protection	Pre-alarm (alarm off after 1 sound), LED Red light on, voltage contiously reduce and shutdown		
Over voltage protection	Pre-alarm (alarm off after 2 sounds), LED Red light on, shutdown		
Overload protection	Continuous alarm, LED Red light on, shutdown		
Over temperature protection	Pre-alarm (alarm off after 3 sounds), temprature continously rise, LED Red light on, shutdown		
Short circuit protection	Perfect protection and no damage the circuit		
Input reverse polarity protection	Fuse burn-out		
Low voltage alarm	10.5±0.5V	21±0.5V	42±1V
Low voltage protection	9.5±0.5V	19±0.5V	38±1V
Over voltage protection	15.5±0.5V	31±0.5V	61±1V
Low voltage recover	13±0.5V	24±0.5V	48±1V
Over voltage recover	14.5V±0.5V	29V±0.5V	58V±1V
Working temperature	-20°- +50°		
Product Dimension(mm)	370*205*85		
Mounting Size(mm)	340*130		
Net./gross weight(kgs)	4.5/5.2		
Gross weight/CTN(kgs)	21.7		
Warranty	24Months		
DC Cable(mm ²)	25	10	6
Cooling method	Intelligent air cooling		

CHOOSE SOCKET



UNIVERSAL



AUSTRALIA



BRITISH



EUROPE



FRENCH




AMERICAN



AMERICAN



SOUTH AFRICA



MORE STYTLE
CHECK WITH SALES

OTHERS